










**INSCHROEFELEMENTEN**

	Vermogen	Spanning	Insteek	Plug afmeting	mat.	artikel	element buis	Voeler buis	Box	Thermostaat °C.	W/cm <sup>2</sup>
	kW		mm					J / N			
ISE 1 	2	230/400V	250	G1½" BSP	Messing	111375	INC 825	J			5,8
	3	230/400V	250	G1½" BSP	Messing	111376	INC 825	J			8,8
	4,5	3x400V	360	G1½" BSP	Messing	101599	INC 825	J			9,2
	5	3x400V	460	G1½" BSP	Messing	103160	INC 825	J			7,7
	6	230/400V	425	G1½" BSP	Messing	103853	INC 825	J			9,7
	7,5	3x400V	520	G1½" BSP	Messing	103870	INC 825	J			10
	7,5	3x400V	700	G1½" BSP	Messing	100868	INC 825	J			7,4
	9	3x400V	470	G1½" BSP	Messing	102712	INC 825	J			13
	9	3x400V	600	G1½" BSP	Messing	104555	INC 825	J			10,3
ISE 2 	6	3x400V	425	G1½" BSP	RVS 316	104405	INC 825	J			9,7
	7,5	3x400V	700	G1½" BSP	RVS 316	100870	INC 825	J			7,4
	9	3x400V	600	G1½" BSP	RVS 316	101911	INC 825	J			10,3
Box Alu-kunststof type S5 ISE 3 	2	230/400V	250	G1½" BSP	Messing	111468	INC 825	J	J	N	5,8
	3	230/400V	250	G1½" BSP	Messing	111469	INC 825	J	J	N	8,8
	4,5	3x400V	360	G1½" BSP	Messing	103564	INC 825	J	J	N	9,2
	5	3x400V	460	G1½" BSP	Messing	111467	INC 825	J	J	N	7,7
	6	3x400V	425	G1½" BSP	Messing	102854	INC 825	J	J	N	9,7
	7,5	3x400V	520	G1½" BSP	Messing	100532	INC 825	J	J	N	10
	7,5	3x400V	700	G1½" BSP	Messing	100912	INC 825	J	J	N	7,4
	9	3x400V	470	G1½" BSP	Messing	113015	INC 825	J	J	N	13
	9	3x400V	600	G1½" BSP	Messing	103280	INC 825	J	J	N	10,3
	6	3x400V	425	G1½" BSP	RVS 316	104408	RVS316L	J	J	N	9,7
	7,5	3x400V	700	G1½" BSP	RVS 316	111482	INC 825	J	J	N	7,4
	9	3x400V	600	G1½" BSP	RVS 316	111483	INC 825	J	J	N	10,3
Box RVS Ø64x62mm ISE 4 	2	230/400V	180	G1½" BSP	Messing	110765	INC 800	J	J	N	10
	2	230/400V	250	G1½" BSP	Messing	106506	INC 800	J	J	N	6
	3	230/400V	250	G1½" BSP	Messing	104931	INC 800	J	J	N	9
Box Alu G113 115x90x55mm ISE 5A 	2	230V	180	G1½" BSP	Messing	107384	INC 825	J	J	30-85	10
	6	3x400V	425	G1½" BSP	Messing	102331	INC 825	J	J	N	9,7
	7,5	3x400V	700	G1½" BSP	Messing	100858	INC 825	J	J	N	7,4
	9	3x400V	600	G1½" BSP	Messing	100785	INC 825	J	J	N	10,3
Box Alu G115 148x108x75mm ISE 5B 	3	3x400V	250	G1½" BSP	Messing	113016	INC 825	J	J	0-40	8,8
	5	3x400V	460	G1½" BSP	Messing	113017	INC 825	J	J	0-40	7,7
	7,5	3x400V	520	G1½" BSP	Messing	102047	INC 825	J	J	0-40	10
	7,5	3x400V	700	G1½" BSP	Messing	100860	INC 825	J	J	60-200	7,4
	9	3x400V	600	G1½" BSP	RVS 316	101775	INC 825	J	J	30-85	10,3

**INSCHROEFELEMENTEN**

	Vermogen	Spanning	Insteek	Plug afmeting	mat.	artikel	element buis	Voeler buis	Box	Thermostaat °C.	W/cm <sup>2</sup>
	kW		mm					J / N			
Box Alu G137 120x120x100mm ISE 6  	2	230V	250	G1½" BSP	Messing	111094	INC 825	J	J	30-90	5,8
	2	230/400V	250	G1½" BSP	Messing	110088	INC 825	J	J	0-40	5,8
	2	230/400V	250	G1½" BSP	Messing	104581	INC 825	J	J	30-110	5,8
	3	230V	250	G1½" BSP	Messing	111268	INC 825	J	J	30-85	8,8
	3	230/400V	250	G1½" BSP	Messing	104516	INC 825	J	J	60-200	8,8
	6	3x400V	425	G1½" BSP	Messing	104479	INC 825	J	J	60-200	9,7
	7,5	3x400V	700	G1½" BSP	Messing	111484	INC 825	J	J	30-85	7,4
	9	3x400V	600	G1½" BSP	Messing	111485	INC 825	J	J	30-85	10,3
	6	3x400V	425	G1½" BSP	RVS 316	102101	INC 825	J	J	30-85	9,7
	Box RVS Gesta 5.1, 105x105x100mm ISE 7A  	2	230/400V	250	G1½" BSP	Messing	111472	INC 825	J	J	N
3		230/400V	250	G1½" BSP	Messing	111473	INC 825	J	J	N	8,8
4,5		3x400V	360	G1½" BSP	Messing	111474	INC 825	J	J	N	9,2
5		3x400V	460	G1½" BSP	Messing	111475	INC 825	J	J	N	7,7
6		3x400V	425	G1½" BSP	Messing	111476	INC 825	J	J	N	9,7
7,5		3x400V	520	G1½" BSP	Messing	111477	INC 825	J	J	N	10
7,5		3x400V	700	G1½" BSP	Messing	111478	INC 825	J	J	N	7,4
9		3x400V	470	G1½" BSP	Messing	111479	INC 825	J	J	N	13
9		3x400V	600	G1½" BSP	Messing	111480	INC 825	J	J	N	10,3
6		3x400V	425	G1½" BSP	RVS 316	111392	INC 825	J	J	N	9,7
7,5		3x400V	700	G1½" BSP	RVS 316	111470	INC 825	J	J	N	7,4
9		3x400V	600	G1½" BSP	RVS 316	111471	INC 825	J	J	N	10,3
Box RVS Gesta 5.1, 105x105x100mm ISE 7B    met thermostaat inwendig		2	230V	250	G1½" BSP	Messing	111486	INC 825	J	J	0-90
	3	230V	250	G1½" BSP	Messing	111487	INC 825	J	J	0-90	8,8
	4,5	3x400V	360	G1½" BSP	Messing	111497	INC 825	J	J	30-90	9,2
	5	3x400V	460	G1½" BSP	Messing	111498	INC 825	J	J	30-90	7,7
	6	3x400V	425	G1½" BSP	Messing	111500	INC 825	J	J	30-90	9,7
	7,5	3x400V	520	G1½" BSP	Messing	111501	INC 825	J	J	30-90	10
	7,5	3x400V	700	G1½" BSP	Messing	111502	INC 825	J	J	30-90	7,4
	9	3x400V	470	G1½" BSP	Messing	111503	INC 825	J	J	30-90	13
	9	3x400V	600	G1½" BSP	Messing	111504	INC 825	J	J	30-90	10,3
	6	3x400V	425	G1½" BSP	RVS 316	111505	INC 825	J	J	30-90	9,7
	7,5	3x400V	700	G1½" BSP	RVS 316	111506	INC 825	J	J	30-90	7,4
	9	3x400V	600	G1½" BSP	RVS 316	111507	INC 825	J	J	30-90	10,3
Box RVS Gesta 5.1, 105x105x100mm ISE 7C    met thermostaat uitwendig	2	230V	250	G1½" BSP	Messing	111508	INC 825	J	J	30-85	5,8
	3	230V	250	G1½" BSP	Messing	111509	INC 825	J	J	30-85	8,8
	4,5	3x400V	360	G1½" BSP	Messing	111510	INC 825	J	J	30-85	9,2
	5	3x400V	460	G1½" BSP	Messing	111511	INC 825	J	J	30-85	7,7
	6	3x400V	425	G1½" BSP	Messing	111512	INC 825	J	J	30-85	9,7
	7,5	3x400V	520	G1½" BSP	Messing	111513	INC 825	J	J	30-85	10
	7,5	3x400V	700	G1½" BSP	Messing	111514	INC 825	J	J	30-85	7,7
	9	3x400V	470	G1½" BSP	Messing	111515	INC 825	J	J	30-85	13
	9	3x400V	600	G1½" BSP	Messing	111516	INC 825	J	J	30-85	10,3

**INSCHROEFELEMENTEN**

	Vermogen	Spanning	Insteek	Plug afmeting	mat.	artikel	element buis	Voeler buis	Box	Thermostaat °C.	W/cm <sup>2</sup>
	kW		mm					J / N			
 met thermostaat uitwendig	6	3x400V	425	G1½" BSP	RVS 316	111517	INC 825	J	J	30-85	9,7
	7,5	3x400V	700	G1½" BSP	RVS 316	111518	INC 825	J	J	30-85	7,4
	9	3x400V	600	G1½" BSP	RVS 316	111519	INC 825	J	J	30-85	10,3
Box RVS Gesta 120x120x120mm ISE 8 	3	1x230V	250	G1½" BSP	Messing	110434	INC 825	J	J	30-85	9,7
	6	3x400V	425	G1½" BSP	RVS 316	110700	INC 825	J	J	N	9,7
	6	3x400V	425	G1½" BSP	RVS 316	110386	INC 825	J	J	0-40	9,7
	6	3x400V	425	G1½" BSP	RVS 316	108032	INC 825	J	J	30-85	9,7
	6	3x400V	425	G1½" BSP	RVS 316	108469	INC 825	J	J	30-110	9,7
Box kunststof, 90x90x110mm ISE 9-WPI IP54 	2,5	230/400V	370	G1½" BSP	Messing	111520	INC 825	J	J	30-75	6,2
	3	230/400V	390	G1½" BSP	Messing	111526	INC 825	J	J	30-75	6,7
	4,5	3x400V	470	G1½" BSP	Messing	111527	INC 825	J	J	30-75	8
	6	3x400V	560	G1½" BSP	Messing	111528	INC 825	J	J	30-75	8,4
	7,5	3x400V	650	G1½" BSP	Messing	111529	INC 825	J	J	30-75	8,7
	9	3x400V	720	G1½" BSP	Messing	111530	INC 825	J	J	30-75 stb98°C	9,3
Box kunststof, 90x90x110mm ISE 10-WP IP54 	2,5	230/400V	350	G1½" BSP	RVS 304	111531	INC 825	J	J	30-75	6,2
	3	230/400V	370	G1½" BSP	RVS 304	111532	INC 825	J	J	30-75	6,9
	4,5	3x400V	420	G1½" BSP	RVS 304	111533	INC 825	J	J	30-75	8,8
	6	3x400V	520	G1½" BSP	RVS 304	111534	INC 825	J	J	30-75	8,9
	7,5	3x400V	620	G1½" BSP	RVS 304	111535	INC 825	J	J	30-75	9
	9	3x400V	700	G1½" BSP	RVS 304	111536	INC 825	J	J	30-75 stb98°C	9,4
ISE 14 	0,2	230V	175	G1" BSPT	RVS 304	111014	RVS 316	J	J	0-90	0,4

- Watt belasting: Water: 5-10W/cm<sup>2</sup> Stromend water: 7-13 W/cm<sup>2</sup> Olie: 0,8-4W/cm<sup>2</sup> (afhankelijk van t)

- Thermostaten 1F, max. 16A: 0-40°C, 0-90°C, 30-85°C, 30-110°C, 60-200°C etc. (zie lijst thermostaten)

- Thermostaten 3F, max. 16A: 0-40°C, 30-85°C, 30-110°C, 60-200°C etc. (zie lijst themostaten)

- Andere vermogens, aansluitspanningen, afmetingen en grote aantallen op aanvraag