







BOILERS + ONDERDELEN DAALDEROP

	Type	Gewicht kg.	Vermogen (kW)	spanning (V)	Artikel
	10 ltr	6,5	0,5	1x208/60Hz "Hot fill"	111449
	10 ltr	6,5	0,5	1x230/50Hz "Hot fill"	101563
	10 ltr	6,5	2,2	1x230/50Hz "Hot fill"	103858
	15 ltr	7,5	1,6	1x110/60Hz	107823
	15 ltr	7,5	2,2	1x230/50Hz	101454
<p>Mono</p>  	30 ltr.	22	0,45	1x230/50Hz	101650
	30 ltr.	22	2,5	1x230/50Hz	106279
	50 ltr.	22,5	2,5	1x230/50Hz	101745
	50 ltr.	22,5	2,5	1x254/60Hz	108938
	50 ltr.	22,5	2,5	3x440/60Hz	106738
	80 ltr.	35	2,5	1x220/50Hz	100911
	80 ltr.	35	5,25	3x220/50Hz (zonder nul)	102217
	80 ltr.	35	5,25	3x380/50Hz (zonder nul)	100578
	80 ltr.	35	5,25	3x400/50Hz (zonder nul)	100668
	80 ltr.	35	5,25	3x415/60Hz (zonder nul)	103892
	80 ltr.	35	5,25	3x440/60Hz (zonder nul)	100545
	80 ltr.	35	5,25	3x480/60Hz (zonder nul)	104227
	120 ltr.	53	5,25	3x220/50Hz (zonder nul)	104775
	120 ltr.	53	5,25	3x380/50Hz (zonder nul)	102466
	120 ltr.	53	5,25	3x400/50Hz (zonder nul)	100544
	120 ltr.	53	5,25	3x415/50Hz (zonder nul)	101248
	120 ltr.	53	5,25	3x440/60Hz (zonder nul)	100756
	120 ltr.	53	5,25	3x480/60Hz (zonder nul)	104228
	120 ltr.	53	6	3x400/50Hz (zonder nul)	102579
	120 ltr.	53	6	3x415/50Hz (zonder nul)	101942
	120 ltr.	53	6	3x440/60Hz (zonder nul)	101302
	120 ltr.	53	7,5	3x440/60Hz (zonder nul)	105351
150 ltr.	55	7,5	3x230/50Hz (zonder nul)	105925	
150 ltr.	55	7,5	3x380/50Hz (zonder nul)	102720	
150 ltr.	55	7,5	3x400/50Hz (zonder nul)	108578	
150 ltr.	55	7,5	3x440/60Hz (zonder nul)	103959	
150 ltr.	55	7,5	3x480/60Hz (zonder nul)	104229	
<p>Toebehoren</p> <p>regel thermostaat 30-85°C</p> <p>max. thermostaat 95°C</p> <p>set Scheepsbeugels</p> <p>set Scheepsbeugels</p> <p>Inlaatcombinatie Ø15 mm</p> <p>Inlaatcombinatie Ø22 mm</p> <p>Aansluitset/afvoerset</p> <p>Pakkingring rubber</p> <p>Pakkingring rubber flensplaatelment</p>  	Mono boilers	0,1		3P, 16A	100072
	Mono boilers	0,1		Hand reset, 3P, 16A	100077
	30/50 ltr	2		RVS uitvoering	100755
	80/120/150 ltr.	3		RVS uitvoering	100754
	Ø15 mm	0,3		Max. 8 BAR.	100546
	Ø22 mm	0,3		Max. 8 BAR.	100547
	Close-in/hotfill	0,5		07.92.64.047	102788
	Hotfill	0,5		T.b.v. Hotfille 10 ltr.	107379
	Mono boilers	0,5		T.b.v. element Mono 30-150 ltr.	100185
	30 ltr.	2	2,5	1x230/50Hz	107110
	50 ltr.	2	2,5	1x230/50Hz	105066
	80 ltr.	2	5,25	3x400/50Hz (zonder nul)	102309
	80 ltr.	2	5,25	3x415/50Hz (zonder nul)	105348
	80 ltr.	2	5,25	3x440/60Hz (zonder nul)	104224
	120 ltr.	2	5,25	3x380/50Hz (zonder nul)	101900
	120 ltr.	2	5,25	3x400/50Hz (zonder nul)	101819
	120 ltr.	2	5,25	3x415/50Hz (zonder nul)	104569
	120 ltr.	2	5,25	3x440/60Hz (zonder nul)	102160
120 ltr.	2	6	3x440/60Hz (zonder nul)	101315	
120 ltr.	2	7,5	3x440/60Hz (zonder nul)	108856	
150 ltr.	3	7,5	3x480/60Hz (zonder nul)	105684	

* Andere vermogens en aansluitspanningen op aanvraag.