

**BOILERS + ONDERDELEN NIBE**

	Type	Gewicht kg.	Vermogen (kW)	spanning (V)	Artikel
<b>Direct verwarmd</b> 	ES 160-160 ltr.	55	4,5	3x440/60Hz (zonder nul)	101786
	ES 160-160 ltr.	55	6	3x400/50Hz (zonder nul)	104789
	ES 210-200 ltr.	70	6	3x400/50Hz (zonder nul)	104155
	ES 210-200 ltr.	70	9	3x400/50Hz (zonder nul)	102598
	ES 210-200 ltr.	70	11	3x440/60Hz (zonder nul)	100759
	ES 300-270 ltr.	85	6	3x400/50Hz (zonder nul)	101902
	ES 300-270 ltr.	85	12	3x440/60Hz (zonder nul)	104412
	ES 300-270 ltr.	85	15	3x440/60Hz (zonder nul)	101550
<b>Indirect verwarmd</b>  Boilervat SP / VPA / EKS	Elkassett ELK 213	18	13	3x400/50Hz (met nul)	102004
	ombouw ELK 213	0	13	3x208/60Hz (zonder nul)	102064
	ombouw ELK 213	0	13	3x380/50Hz (zonder nul)	102856
	ombouw ELK 213	0	13	3x400/50Hz (zonder nul)	104833
	ombouw ELK 213	0	13	3x440/60Hz (zonder nul)	101841
	ombouw ELK 213	0	13	3x480/60Hz (zonder nul)	102002
	Montage ELK213 op SP300(incl. druktest)	170	13		110152
	SP 300	150	300 ltr.		102725
	VPA 300/200	208	300 ltr.		105117
	VPA 450/300	285	450 ltr.		104485
	EKS 300 EX	108	300 ltr.		109358
	EKS 500 EX	160	500 ltr.		104541
	EKS 1000 EX	235	990 ltr.		111650
	EKS 500	160	500 ltr.		104541
	EKS 750	185	740 ltr.		110772
	EKS 1000	235	990 ltr.		105174
<b>Toebehoren</b> Set scheepsbeugels 160-300 Ltr. Pakkingring rubber ELK 213 Set motageflenzen ELK 213 Regelthermostaat 30-85°C, 3P 16A Max. thermostaat 110°C, 3P 16A Flensplaatelment  Inschroefelement Dompelbuis koper 280x10mm	ES-24	3			101551
	ELK 213	0,5			108466
	ELK 213	1			102005
	ELK 213	1			109730
	Hand reset	1			106200
	ELK 213	4	13	3x208/60Hz (zonder nul)	104965
	ELK 213	4	13	3x400/50Hz (zonder nul)	101862
	ELK 213	4	13	3x440/60Hz (zonder nul)	104147
	ELK 213	4	13	3x480/60Hz (zonder nul)	104385
	EKS	5	9	3x440/60Hz (zonder nul)	105599
	EKS / EKL	1			104542

\* Andere vermogens en aansluitspanningen op aanvraag.